



SPECIFICATIONS

10846 79' PRO® AerialCat Ladder | Retail Unit

CHASSIS

- Panther™ XLFD with 10" Raised Roof
- Steertek Front Axle

DRIVE TRAIN

- Cummins L9 450 HP Engine
- Allison 3000 EVS Transmission

PUMP & PLUMBING

- 500 Gallon Water Tank
- Waterous CX 1500 GPM Pump
- PRO® Series Pump Panel

BODY

- 79' PRO® AerialCat Body Constructed of 1/8" Aluminum
- Minimum of 115 feet of Ground Ladders
- 438 Total Cubic Feet of Compartmentation
- Hosebed Capacity of 1000' of 5"

ELECTRICAL

- Class 1 Multiplex System
- Vitruval Dash Display
- IQAN Aerial Motion Control System

AERIAL

- Vertical Reach: 79'
- Horizontal Reach: 70'
- Operation Range: -7° to +80°
- Payload: 500lbs Wet / 500lbs. Dry Unrestricted
- Wind & Ice Rating: 1/4" Ice & 50 mph Wind
- Stabilizers: One (1) set H Style
- Stabilizer Spread: 16'

DIMENSIONS

- Overall Height: 138" (11'-6")
- Overall Length: 442" (36'-10")
- Wheelbase: 232"

